



Operating Conditions/工作条件:

Prssure/压力: ≤ 10 Bar

Temperature/温度: $-20^{\circ}\text{C} \sim 180^{\circ}\text{C}$

Speed/线速度: $\leq 12\text{m/s}$.

Materials/材料:

Face/密封面: Carbon, SIC, TC

Seat/静环: Ceramic, SIC, TC

Secondary Sealing/辅助密封: NBR, EPDM, Viton

Metal/金属: 304SS, 316SS

SIZE	d	D	D1	L1	L2
0.500	12.700	24.0	25.4	20.8	7.9
0.625	15.875	26.7	31.8	22.5	10.3
0.750	19.050	31.2	34.9	22.5	10.3
0.875	22.225	33.5	38.1	24.0	10.3
1.000	25.400	43.2	41.3	25.5	11.1
1.125	28.575	46.5	44.5	27.0	11.1
1.250	31.750	49.5	47.6	27.0	11.1
1.375	34.925	52.7	50.8	29.0	11.1
1.500	38.100	56.0	53.9	29.0	11.1
1.625	41.275	62.2	63.3	35.0	12.7
1.750	44.450	66.0	63.5	35.0	12.7
1.875	47.625	66.0	66.7	38.3	12.7
2.000	50.800	73.0	69.9	38.3	12.7
2.125	53.975	73.5	76.2	43.0	14.2
2.250	57.150	79.6	79.4	43.0	14.2
2.375	60.325	82.0	82.6	46.2	14.2
2.500	63.500	85.0	85.7	46.2	14.2
2.625	66.675	88.5	85.7	49.5	15.9
2.750	69.850	92.7	88.9	49.5	15.9
2.875	73.025	95.0	95.3	52.5	15.9
3.000	76.200	102.0	98.4	52.5	15.9

		昆山福步工业设备有限公司 FBU INDUSTRIAL EQUIPMENT (KUNSHAN) CO., LTD	
项目/Item 设计/Design 施伟/Leo Shi		材料/Material 规格型号/TYPE NO. BW21-XXXX	
备注/Remark 日期/Date 2021/8/12		质量/Weight 名称/Name 机械密封/Mech. seal	
审核/Checked		版本: Rev. A 物料编码/Code	